



# Configure your own Control Station

## Area of information

ZONING			
GAS	1	2	
DUST	21	22	
EXPLOSION GROUP			
	IIA	IIB	IIC
TEMPERATURE CLASS			
	T4	T5	T6
TEMPERATURE			
AMBIENT	°C	-	°C UP TO + °C

**RATED VOLTAGE:**

**MODE OF PROTECTION:**

EXD	EXE	EXI	OTHER:
ALUMINUM		STAINLESS STEEL	GRP

**NUMBER OF ACTUATORS ON FRONT SIDE:**

LEGEND		REQUIREMENTS		
		OPERATOR	COLOR	CONTACTS/POLES
1	PUSH BUTTON MOMENTARY			
2	PUSH BUTTON STEADY			
3	EMERGENCY P.B.			
4	2 POS. SELECTOR			
5	3 POS. SELECTOR			
6	KEY SELECTOR SWITCH			
7	PILOT LIGHT			
8	SPECIAL SELECTOR (PROVIDE DIAGRAM)			
9	METER: TO BE SPECIFIED			
10	OTHER: TO BE SPECIFIED			

**WIRING:**

YES NO ( DIRECT WIRING)

**ENTRY SPECIFICATION:**

ENCLOSURE SIDE	TAILLE	METRIC												INCHES											
		M20- 1/2"				M25 - 3/4"				M32 - 1"				M40 - 1 1/2"				M50 - 1 1/4"				M63 - 2"			
		A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
POLY GLAND																									
METAL GLAND																									
ARMOURED GLAND																									
POLY PLUG																									

**COMPLEMENTARY INFORMATION:**

CABLE ARME OU NON  
TERRE TRAVERSANTE

**CONTACT DETAILS:**

REQUEST FOR QUOTATION	REQUEST FOR SALES ENGINEER VISIT
NAME: _____	PHONE NUMBER : _____
COMPANY: _____	FAX NUMBER : _____
EMAIL ADDRESS : _____	COMMENTS : _____
ADDRESS : _____	_____
_____	_____