



Lighting requirements

Area of information

ZONING

GAS	1	2
DUST	21	22

EXPLOSION GROUP

IIA	IIB	IIC
-----	-----	-----

TEMPERATURE CLASS

T1	T2	T3	T4	T5	T6
----	----	----	----	----	----

TEMPERATURE

AMBIENT	°C	-	°C	UP TO	+	°C
---------	----	---	----	-------	---	----

RATED VOLTAGE:

VOLTAGE	V	FREQUENCY	HZ
---------	---	-----------	----

MODE OF PROTECTION:

EXD	EXE	OTHER:
-----	-----	--------

MATERIAL:

ALUMINIUM	STAINLESS STEEL
-----------	-----------------

TYPE OF LAMP:

FLUORESCENT	SODIUM
METAL HALIDE	MERCURY
HALOGEN	LED

IP:

65	66	67
----	----	----

TYPE OF LIGHTING:

1 TUBE	LANTERN/ WELLGLASS	
2 TUBES	FLOODLIGHT	
POWER NEEDS:	W	LED lm

MOUNTING SUPPORT:

WALL	CEILING	POLE
------	---------	------

EMERGENCY VERSION:

YES	DURATION TIME	60 MIN	90 MIN	120 MIN	180 MIN
-----	---------------	--------	--------	---------	---------

ENTRY SPECS:

Number of Entries				
Size needed	M20	M25	M32	M40
Armoured cable	Yes		No	
Cable detail				

CONTACT DETAILS:

REQUEST FOR QUOTATION	REQUEST FOR SALES ENGINEER VISIT
NAME: _____	PHONE NUMBER : _____
COMPANY: _____	FAX NUMBER : _____
EMAIL ADDRESS : _____	COMMENTS : _____
ADDRESS : _____	_____
_____	_____